



Rapid Recovery Griddles

Heavy Duty Gas Griddles - ASTM F1275 Performance Testing & Efficiency Comparison

Device		Energy Input Rate		Preheat to 375F			Idle Energy	Heavy Load Cooking Energy Efficiency (24 Hamburgers)				
Mfg	Model #	Rated Energy (Btu/h)	Measured Energy Input (Btu/h)	Duration (Min.)	Gas Energy Consumption (Btu/h)	Preheat Rate (°F/min)	Gas Idle Energy Rate (Btu/h)	Cook Time (min)	Average Recovery Time (min)	Gas Cooking Energy Rate (Btu/h)	Heavy Load Cooking Efficiency (%)	Production Capacity (lb/hr)
Vulcan	36RRG	82,500	83,444	9.58	12,197	31.6	15,107	6.25	< 1.0	56,627	40.5	49.3
Garland	CG36	90,000	85980	13.27	18,780	22.8	17,465	6.80	< 1.0	54,582	40.7	46.2
US Range	RGTSA	72,000	71,622	15.60	20,988	16.4	17,449	8.47	2.42	45,869	34.1	33.2
Wells	WG2436G	75,000	72,955	10.75	12,266	27.7	16,378	7.75	3.20	40,692	39.5	33.0
Lang	GG3	81,000	81,896	21.90	27,264	13.9	21,400	7.50	< 1.0	60,780	31.7	43.2
Star	836TSCHS	90,000	92,171	12.00	18,300	25.1	11,099	7.93	1.16	49,083	37.2	39.8
Magikitch'n	MKG-36	90,000	93,275	14.90	22,667	25.2	19,601	7.84	< 1.0	54,783	35.7	41.3

Note: All data presented is published at www.fishnick.com/publications/appliancereports/griddles



Vulcan RRG models are available in 24", 36", 48" & 60" models.

Vulcan RRE models are available in 24", 36" and 48" models.

Note: 24" models do not carry the Energy Star certification.

